





**Gaskets, Inc.**  
301 W. Hwy. 16  
Rio, WI 53960-0398  
**800-558-1833**  
FAX 920-992-3124  
www.gasketsinc.com  
info@gasketsinc.com

## Product Data Sheet — GT20C


### Tadpole Types: 1, 2, 3, 8, & 9




**TYPE 1**



**TYPE 2**



**TYPE 3**



**TYPE 8**

**Custom  
Design**

**TYPE 9**

<b>Description:</b>	High-Performance Coated Fiberglass tadpole seal with 304 Stainless Steel Hollow Core.
<b>Size:</b>	Standard and custom sizes available. See Tadpole Types and potential sizes listed above.
<b>Cover:</b>	1/16" thick premium quality coated woven fiberglass tape and cloth blue in color.
<b>Core:</b>	304 Stainless steel Hollow Core.
<b>Temperature:</b>	1200° F / 649° C
<b>Application:</b>	Tadpole seals are used in sealing oven doors, covers, ducts, dampers, panel joints and other applications where conformance to uneven flanges is required.
<b>Chemical Resistance:</b>	Fiberglass textiles and stainless steel have excellent resistance to most chemicals. Please call Gaskets Incorporated for specific application concerns.
<b>Other:</b>	Coated Fiberglass increases the temperature resistance over that of uncoated fiberglass textile products. Tensile abrasion resistance strength and stainless steel have excellent mechanical properties. They are resilient, have excellent resistance to thermal shock, vibration, and to most chemicals. They are used in a variety of industrial applications requiring superior temperature and insulation performance.