



Gaskets, Inc.
301 W. Hwy. 16
Rio, WI 53960-0398
800-558-1833
FAX 920-992-3124
www.gasketsinc.com
info@gasketsinc.com

Product Data Sheet — GF011, GF011PSA & GF011DW

Description:

High-Performance Heat Treated Fiberglass Tape GF011, GF011PSA (Pressure Sensitive Adhesive back) or GF011DW (Drop Warp tape, also known as ladder tape or bolt hole tape).

Material

100% premium heat-treated woven fiberglass

Non-Flammable

Products will not burn, smolder, or support flame

High Heat Resistance

Remains stable to 1000° F/538°C, good abrasion resistance and resistance to direct flame

Excellent Dimensional Stability

Will not stretch or shrink. Retains stability even at high temperatures

High Tensile Strength

Good strength to weight ratio

Chemical Resistance

Highly resistant to most chemicals and solvents. Except Hydrofluoric and hot Phosphoric acid and wet Hydrogen Chloride. Will not rot or mildew

Excellent Electrical Properties

High dielectric strength and low constants

Size

Fiberglass tapes are available 1/32", 1/16", 1/8" and 1/4" thicknesses and 1/2", 3/4", 1", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 7", 8", 9", 10", 11", & 12" widths. Depending on the combination, Gaskets, Incorporated has many sizes available in stock. All are sold in 100 foot rolls only. Call us toll free to see if we have the thickness and width you are looking for.