





Gaskets, Inc.
301 W. Hwy. 16
Rio, WI 53960-0398
800-558-1833
FAX 920-992-3124
www.gasketsinc.com
info@gasketsinc.com

Product Data Sheet — GT12D


Tadpole Types: 1, 2, 3, 8, & 9




TYPE 1



TYPE 2



TYPE 3



TYPE 8

**Custom
Design**

TYPE 9

Description	PTFE-coated fiberglass tadpole
Size:	Standard and custom sizes available. See Tadpole Types and potential sizes listed above.
Cover:	1/16" Thick Premium quality heat-treated woven Fiberglass Tape coated with PTFE.
Core:	Inconel® Stainless Steel solid mesh
Temperature:	From -100° to + 500° F / -38° to + 260° C operating range will not become stiff or brittle.
Application:	Tadpole seals are used to seal oven doors, covers, ducts, dampers, panel joints and other applications where conformance to uneven flanges is required.
Chemical Resistance:	Completely resistant to all solvents, acids, fuels, weathering, moisture, mildew, and chemicals except molten alkali metals, fluorine at high temperature and certain complex halogen compounds.
Other:	PTFE Coated Fiberglass and Inconel® Stainless steel have excellent mechanical properties. They are resilient, have excellent resistance to thermal shock, vibration, and to most chemicals. They are used in a variety of industrial applications requiring superior temperature and insulation performance.