





Gaskets, Inc.
301 W. Hwy. 16
Rio, WI 53960-0398
800-558-1833
FAX 920-992-3124
www.gasketsinc.com
info@gasketsinc.com

Product Data Sheet — GT22M


Tadpole Types: 1, 2, 3, 8, & 9




TYPE 1



TYPE 2



TYPE 3



TYPE 8

**Custom
Design**

TYPE 9

Description

Viton® coated fiberglass cover with Fiberglass core.

Size:

Standard and custom sizes available. See Tadpole Types and potential sizes listed above. Minimum bulb diameter (C) is ¼", Maximum diameter is 3". The minimum overall width (D) is equal to C + ½ inch. There is no (reasonable) overall maximum (D) dimension.

Cover:

.060" Thick Viton® 100% Fluoroelastomer coated Fiberglass.

Core:

Fiberglass knitted rope

Temperature:

From 0° to 500° F / 32° to 260° C operating range will not become stiff or brittle.

Application:

Tadpole seals are used in sealing oven doors, covers, ducts, dampers, panel joints and other applications where conformance to uneven flanges is required. Because Viton® offers excellent resistance to fuel, and hydrocarbon based fluids, it is often the material of choice for use in clean rooms. Viton® does not out-gas and this feature makes it ideal for paint room installations.

Chemical Resistance:

Highly resistant to most solvents, acids and fuels. Please consult a chemical resistance guide for a complete list or contact Gaskets, Inc. for application and selection guidance and/or resistance information.