





**Gaskets, Inc.**  
301 W. Hwy. 16  
Rio, WI 53960-0398  
**800-558-1833**  
FAX 920-992-3124  
www.gasketsinc.com  
info@gasketsinc.com

## Product Data Sheet — GT23D


### Tadpole Types: 1, 2, 3, 8, & 9




**TYPE 1**



**TYPE 2**



**TYPE 3**



**TYPE 8**

**Custom  
Design  
TYPE 9**

<b>Description:</b>	High-Performance Coated Fiberglass tadpole seal with Inconel® Steel Solid Mesh Core.
<b>Size:</b>	Standard and custom sizes available. See Tadpole Types and potential sizes listed above.
<b>Cover:</b>	1/16" thick premium quality woven fiberglass tape and/or cloth impregnated with Vermiculite, tan in color.
<b>Core:</b>	Inconel® Steel Solid Mesh
<b>Temperature:</b>	1200° F / 649° C
<b>Application:</b>	Tadpole seals are used in sealing oven doors, covers, ducts, dampers, panel joints and other applications where conformance to uneven flanges is required.
<b>Chemical Resistance:</b>	Vermiculite impregnated fiberglass textiles and Inconel® steel have excellent resistance to most chemicals. Both are extremely durable and abrasion resistant. Please call Gaskets Incorporated for specific application concerns.
<b>Other:</b>	Vermiculite Impregnated Fiberglass increases the temperature resistance over that of uncoated fiberglass textile. Inconel® Steel increases tensile strength and abrasion resistance over stainless steel. Combined they make a resilient combination with excellent resistance to thermal shock, vibration, and most chemicals. They are used in a variety of industrial applications requiring superior temperature and insulation performance.