





Gaskets, Inc.
301 W. Hwy. 16
Rio, WI 53960-0398
800-558-1833
FAX 920-992-3124
www.gasketsinc.com
info@gasketsinc.com

Product Data Sheet — GT23L


Tadpole Types: 1, 2, 3, 8, & 9




TYPE 1



TYPE 2



TYPE 3



TYPE 8

**Custom
Design**

TYPE 9

| | |
|-----------------------------|--|
| Description: | High-Performance Vermiculite Fiberglass tadpole seal with Ceramic core. |
| Size: | Standard and custom sizes available. See Tadpole Types and potential sizes listed above. |
| Cover: | 1/16" thick premium quality heat-treated woven fiberglass tape and cloth impregnated with vermiculite for increased temperature performance. Tan in color. |
| Core: | Ceramic Core. |
| Temperature: | 1200° F / 649° C |
| Application: | Tadpole seals are used in sealing oven, dryer, and other process heating equipment doors, covers, ducts, dampers, and panel joints. Tadpole seals can solve most high temperature application challenges when conformance to uneven flanges and surfaces is required. |
| Chemical Resistance: | Vermiculite Fiberglass textiles and ceramic rope have excellent resistance to most chemicals. Please call Gaskets Incorporated for specific application concerns. |
| Other: | Vermiculite Fiberglass increases the temperature resistance tensile strength and abrasion resistance over that of regular fiberglass products. They are resilient, have excellent resistance to thermal shock, vibration, and to most chemicals. These seals are used in a variety of industrial applications requiring superior temperature and insulation performance. |