





Gaskets, Inc.
301 W. Hwy. 16
Rio, WI 53960-0398
800-558-1833
FAX 920-992-3124
www.gasketsinc.com
info@gasketsinc.com

Product Data Sheet — GT23M


Tadpole Types: 1, 2, 3, 8, & 9




TYPE 1



TYPE 2



TYPE 3



TYPE 8

**Custom
Design**

TYPE 9

Description:	High-Performance Coated Fiberglass tadpole seal with Fiberglass rope core.
Size:	Standard and custom sizes available. See Tadpole Types and potential sizes listed above.
Cover:	1/16" thick premium quality heat-treated woven fiberglass tape and cloth coated with vermiculite for increased temperature performance. Tan in color.
Core:	Fiberglass Rope Core.
Temperature:	1000° F / 538° C
Application:	Tadpole seals are used in sealing oven doors, covers, ducts, dampers, panel joints and other applications where conformance to uneven flanges is required.
Chemical Resistance:	Fiberglass textiles and ropes have excellent resistance to most chemicals. Please call Gaskets Incorporated for specific application concerns.
Other:	Coated Fiberglass increases the temperature resistance over that of uncoated fiberglass textile products. Tensile abrasion resistance strength and stainless steel have excellent mechanical properties. They are resilient, have excellent resistance to thermal shock, vibration, and to most chemicals. They are used in a variety of industrial applications requiring superior temperature and insulation performance.