




**Gaskets, Inc.**  
301 W. Hwy. 16  
Rio, WI 53960-0398  
**800-558-1833**  
FAX 920-992-3124  
www.gasketsinc.com  
info@gasketsinc.com

## Product Data Sheet — GT25G

### Tadpole Types: 1, 2, 3, 8, & 9



**Custom  
Design**

**TYPE 9**

**Description**

Crease and tear resistant PTFE-coated film on fiberglass cover with an Galvanized solid mesh core.

**Size:**

Standard and custom sizes available. See Tadpole Types and potential sizes listed above.

**Cover:**

.010" Thick crease and tear resistant PTFE coated Fiberglass.

**Core:**

Galvanized solid mesh core

**Temperature:**

From -100° to +500° F / -73° to +260° C operating range will not become stiff or brittle.

**Application:**

Tadpole seals are used in sealing oven doors, covers, ducts, dampers, panel joints and other applications where conformance to uneven surfaces is required. PTFE is very effective in clean room applications and because it performs well at significantly low temperatures it is widely used in Cryogenic applications.

**Chemical Resistance:**

Completely resistant to all solvents, acids, fuels, weathering, moisture, mildew, and chemicals except molten alkali metals, fluorine at high temperature and certain complex halogen compounds.

**Other:**

PTFE Coated Fiberglass and Galvanized wire have excellent mechanical properties. They are resilient and have excellent resistance to thermal shock, vibration, and to most chemicals. They are used in a variety of industrial applications requiring superior temperature and insulation performance.