







**Gaskets, Inc.**  
301 W. Hwy. 16  
Rio, WI 53960-0398  
**800-558-1833**  
FAX 920-992-3124  
www.gasketsinc.com  
info@gasketsinc.com

## Product Data Sheet — GT12C

### Tadpole Types: 1, 2, 3, 8, & 9



**Custom  
Design  
TYPE 9**

<b>Description</b>	PTFE-coated fiberglass tadpole seal with Stainless Steel hollow core.
<b>Size:</b>	Standard and custom sizes available. See Tadpole Types and potential sizes listed above.
<b>Cover:</b>	1/16" Thick Premium quality heat-treated woven Fiberglass Tape coated with PTFE.
<b>Core:</b>	304 Stainless steel hollow-core
<b>Temperature:</b>	From -100° to +500° F /-73C° to +260° C operating range will not become stiff or brittle.
<b>Application:</b>	Tadpole seals are used in sealing oven doors, covers, ducts, dampers, panel joints and other applications where conformance to uneven flanges is required. Its unique ability to stand up under extreme cold makes this PTFE seal is a perfect choice for Cryogenic applications.
<b>Chemical Resistance:</b>	Completely resistant to all solvents, acids, fuels, weathering, moisture, mildew, and chemicals except molten alkali metals, fluorine at high temperature and certain complex halogen compounds.
<b>Other:</b>	PTFE Coated Fiberglass and stainless steel have excellent mechanical properties. They are resilient, have excellent resistance to thermal shock, vibration, and to most chemicals. They are used in a variety of industrial applications requiring superior temperature and insulation performance.